



PRODUCT INFORMATION:

Nominal heat output: 10 kW
 Energy efficiency: 81 %
 CO%: 0,1 %

PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
DEKO 5LC	703310-1	560	1468
DEKO 5LW	703310-2	655	1468
DEKO 5LM	703310-3	845	1468
DEKO 5RC	703320-1	560	1468
DEKO 5RW	703320-2	655	1468
DEKO 5RM	703320-3	845	1468

PRODUCT INFORMATION

	FIREWOOD	FLUE CALCULATION VALUES ⁽¹⁾				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Length [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Deko	33	294	-12	9,5	180	380

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]
	round Ø
Deko	180-210

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	CE-approval according to EN 13240			
	Behind	On the sides	In the radiation area of the door	Front
Deko	150	150	750	1000

¹⁾ The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards.

Take a notice of the countryspecific approvals in section 3

NOTES!

The flue heat category required by the fireplace is T600.

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue.

Country- and region-specific regulations must be adhered to when installing the fireplace