




LATUS L




LATUS L PL




LATUS L G




LATUS L PL G




LATUS R




LATUS R PL



LATUS-1



LATUS R G



LATUS R PL G

PRODUCT INFORMATION:

Thermal energy:	56,4 kWh,	PL: 56,4 kWh
Energy efficiency:	84 %,	PL: 84 %
CO%:	0,09 %,	PL: 0,09 %
Heat storage capacity:		
	100% after 7,3 hours,	PL: after 7,3 hours
	50% after 27,4 hours,	PL: after 27,4 hours
	25% after 50,2 hours,	PL: after 50,2 hours

PRODUCT NUMBER:

Product	Product number	Weight kg	Height mm
LATUS R/L	2TLR / 2TLL	1920	1536
LATUS-1	2TL-1	1930	1536
LATUS R/L PL	2TLRP / 2TLLP	1930	1536
LATUS R/L G	2TLRG / 2TLLG	1950	1536
LATUS R/L PL G	2TLRPG / 2TLLPG	1960	1536

NEEDED FOR ASSEMBLY:

* Mortar 2 x 25 kg (not included in NunnaUuni delivery)

NOTE!

See the product pictures of PL, glass models (G) and Latus R models from the 3pdf!

PL = Top connection

PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø	Temperature °C
Latus R/L / Latus R/L G	-	-	33	16	-	213	-12	21	160	285
Latus R/L PL / Latus R/L PL G	-	-	33	16	-	213	-12	21	180	285

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Latus R/L / Latus R/L G	-	x	x	160-210	150-180	210	1410	370	-	920006	70-100
Latus R/L PL / Latus R/L PL G	-	-	-	180	-	-	-	370	-	920006	70-100

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Latus R/L / Latus R/L G	50	150	200	1000
Latus R/L PL / Latus R/L PL G	50	150	200	1000

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

Take a notice of the countryspecific approvals in section 3

NOTES!

The flue heat category required by the fireplace is T400.

The recommended minimum flue height is 5 m with Ø180 mm. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

Country- and region-specific regulations must be adhered to when installing the fireplace

