




# HESTIA SOLO TUNNEL




HESTIA SOLO TUNNEL



HESTIA SOLO TUNNEL G



HESTIA SOLO 180 TUNNEL



HESTIA SOLO 180 TUNNEL G

## PRODUCT INFORMATION:

<b>Thermal energy:</b>	59,6 kWh
<b>Energy efficiency:</b>	86 %
<b>CO%:</b>	0,09 %
<b>Heat storage capacity:</b>	
	100 % after 6,8 hours
	50 % after 22,4 hours
	25 % after 36,3 hours

## PRODUCT NUMBER:

Product	Product number	Weight kg	Height mm
HESTIA SOLO TUNNEL	2ST	1635	1824
HESTIA SOLO TUNNEL G	2STG	1665	1824
HESTIA SOLO 180 TUNNEL	2ST180	1635	1824
HESTIA SOLO 180 TUNNEL G	2STG180	1665	1824

## NEEDED FOR ASSEMBLY:

\* Mortar 1 x 25 kg (not included in NunnaUuni delivery)

### NOTE!

See the product pictures of glass models (G) and 180 Tunnel model from the 3pdf:stä.

## PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Hestia Solo Tunnel / Hestia Solo Tunnel G Hestia Solo 180 Tunnel / Hestia Solo 180 Tunnel G	384	356	33	16	-	201	-12	19	160	321

## FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Hestia Solo Tunnel / Hestia Solo Tunnel G Hestia Solo 180 Tunnel / Hestia Solo 180 Tunnel G	-	x	x	160-210	150-180	250	350	370	-	920006	70-100

## SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Hestia Solo Tunnel / Hestia Solo Tunnel G Hestia Solo 180 Tunnel / Hestia Solo 180 Tunnel G	1000	200	200	1000

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

### Take a notice of the countryspecific approvals in section 3

#### NOTES!

The flue heat category required by the fireplace is T400.

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

### Country- and region-specific regulations must be adhered to when installing the fireplace

